



ENLARGED VIEW

PEM NUTS FOR COMPONENT MOUNTING DO NOT EXTEND MORE THAN 0.25" BEYOND PANEL SURFACE

INPUT POWER TERMINALS

MTG HOLE 0.438" DIA (6PLCS)

AIR FLOW DIRECTION

AIR FLOW DIRECTION

IF BOTTOM OF ENCLOSURE IS NOT VENTILATED, MOUNT 50 & 100AMP PANELS A MINIMUM OF 6" FROM THE BOTTOM OF THE ENCLOSURE TO ALLOW FOR PROPER AIR FLOW.

HEAT LOSSES = 900 WATTS
AIRFLOW REQ. = 375 CFM

<p>UNLESS OTHERWISE SPECIFIED: ALL DIMENSIONS ARE IN INCHES PER ASME Y14.5M-1994 TOLERANCES: .XX ±.03 .XXX ±.015 ANGLES ±.1° THIRD ANGLE PROJECTION</p>		<p>SCALE 1:1</p>	<p>DATE 02/28/2019 DWG DLL ENGR PL</p>	<p>MESTA ELECTRONICS, INC. CUSTOMER MESTA ELECTRONICS CUST ORDER STD</p>	<p>TITLE 50AMP DPM 3rd GEN ACTIVE FILTER PANEL LAYOUT DWG NO 46000028 REV - CADD FILE 46000028-1 SHEET NO 1 OF 1</p>
<p>THIS DRAWING AND ALL INFORMATION CONTAINED HEREIN IS THE PROPERTY OF MESTA ELECTRONICS, INC. AND MAY NOT BE COPIED, REPRODUCED, OR DIVULGED TO UNAUTHORIZED PERSONS WITHOUT THE WRITTEN PERMISSION OF MESTA ELECTRONICS, INC. FOR THE CONVENIENCE OF THE USER AND SHALL BE RETURNED UPON REQUEST. ©1999 MESTA ELECTRONICS ALL RIGHTS RESERVED</p>		<p>REVISIONS</p>			