



ENLARGED VIEW

PEM NUTS FOR COMPONENT MOUNTING DO NOT EXTEND MORE THAN 0.25" BEYOND PANEL SURFACE

INPUT POWER TERMINALS

MTG HOLE
0.438" DIA
(6PLCS)

HEAT LOSSES = 2500 WATTS
AIRFLOW REQ. = 800 CFM

<p>UNLESS OTHERWISE SPECIFIED: ALL DIMENSIONS ARE IN INCHES PER ANSI Y14.5M-1994 TOLERANCES: .XX ±.03 .XXX ±.015 ANGLES ±.1° THIRD ANGLE PROJECTION</p>		<p>SCALE 1:1</p>	<p>DATE 02/28/2019 DTR DLL ENR PL</p>	<p>MEI MESTA ELECTRONICS, INC. CUSTOMER MESTA ELECTRONICS CUST. ORDER STD</p>	<p>TITLE 150AMP DPM 3rd GEN ACTIVE FILTER PANEL LAYOUT DWG NO 46000026 REV - CADD FILE 46000026-1 SHEET NO 1 OF 1</p>
<p>THIS DRAWING AND ALL INFORMATION CONTAINED HEREIN IS THE PROPERTY OF MESTA ELECTRONICS, INC. AND MAY NOT BE COPIED, REPRODUCED, OR DIVULGED TO UNAUTHORIZED PERSONS WITHOUT THE WRITTEN PERMISSION OF MESTA ELECTRONICS, INC. FOR THE CONVENIENCE OF THE USER AND SHALL BE RETURNED UPON REQUEST. ©1999 MESTA ELECTRONICS ALL RIGHTS RESERVED</p>					
<p>REVISIONS</p>					