



ENLARGED VIEW

PEM NUTS FOR COMPONENT MOUNTING DO NOT EXTEND MORE THAN 0.25" BEYOND PANEL SURFACE

INPUT POWER TERMINALS

MTG HOLE
0.438" DIA
(6PLCS)

HEAT LOSSES = 5100 WATTS
AIRFLOW REQ. = 1300 CFM

TITL 500AMP DPM 2ND GEN
ACTIVE FILTER
PANEL LAYOUT
DWG NO 46000021
REV -
CADD FILE 46000021-1
SHEET NO 1 OF 1

MEI
MESTA ELECTRONICS, INC.
CUSTOMER MESTA ELECTRONICS
CUST ORDER STD
NUMBER

SCALE 1:1
DATE 03/26/14
DTR DLL
ENR PL

UNLESS OTHERWISE SPECIFIED:
ALL DIMENSIONS ARE IN INCHES
INTERFERENCES ARE PER
ASME Y14.5M-1994
TOLERANCES: .XX ±.03
.XXX ±.015
ANGLES ±.1°
THIRD ANGLE
PROJECTION

THIS DRAWING AND ALL INFORMATION
HEREON IS THE PROPERTY OF
MESTA ELECTRONICS, INC. AND MAY NOT BE
COPIED, REPRODUCED, OR DIVULGED TO
UNAUTHORIZED PERSONS WITHOUT THE
WRITTEN CONSENT OF MESTA ELECTRONICS,
INC. ALL RIGHTS ARE RESERVED.
FOR THE CONVENIENCE OF THE USER AND
SHALL BE RETURNED UPON REQUEST.
©1999 MESTA ELECTRONICS ALL RIGHTS
RESERVED

REVISIONS